Head, Producement Unit

REQUEST FOR QUOTATION (RFQ) No. 319-2023

Procurement Unit

The Tarlac State University (TSU), through its Bids and Awards Committee (BAC) and Procurement Unit, will undertake an **Alternative Method of Procurement through Negotiated Procurement** for the items stated below, in accordance with **Section 53.9 Small Value Procurement** of the Revised Implementing Rules and Regulations of Republic Act. No. 9184.

The TSU hereinafter referred to subject below:	o as "the Buyer", now requests s	submission of	a price quotation for the
Purchase Request No.	DESCRIPTION/PARTICU	JLARS	APPROVED BUDGET FOR THE CONTRACT (ABC) inclusive of VAT
2023-05-182 (PROC)	VARIOUS PHOTOGRAPHIC PAR AND ACCESSORIE		483,000.00
Purpose: Photographic Parts, Sup		arter 2023	
Philgeps Posting: Active Date Closing D	te: 5/24/23 ate: 5/19/22	Category: Reference	No.: 9779368
Interested suppliers are require	ed to submit the following docum ayor's / Business Permit	Latest Inco	ome / Business Tax Return Sworn Statement if applicable
2. Bid Validity: 3. Delivery Site: Sup (045 4. Warranty shall be	calendar days from sure ply and Property Management () 606-8159 / (045) 982-2605 for a period minimum of three () after acceptance by the procuri	bmission of bid Unit, Tarlac Sta (3) months of e	ate University expendable supplies, or a
Award of contract shall be made comply with the minimum technique.	le to the bidder with the lowest onical specifications and other te	quotation for th	e subject goods which ions stated herein.
Any alteration, erasures, or ove or his/her duly authorized repre	erwriting shall be valid only if the esentative.	ey are signed o	or initialed by the bidder
than $\frac{5h1/l7}{}$ at the Pro	e Quotation Form (Attachment curement Unit, Admin Building a e manually or through email at t	Tarlac State Ui	niversity, Tarlac City.
portion for every day of delay.	s one tenth (1/10) of one (1) pe Once the cumulative amount one procuring entity shall rescind s open to it.	f liquidated dar	mages reaches ten (10%)
The TSU reserves the right to contract in accordance with Se to the affected bidder or bidder	reject any and all bids, declare a ction 41 of R.A 9184 and its IRI s.	a failure of bido R, without ther	ding, or not award the eby incurring any liability

Form No.: TSU-PRO-SF-06 Revision No.: 06 Effectivity Date: March 5, 2020 Page 1 of 7

Date:	5/18/2023
RFQ No.	319-2023
PR No.	2023-05-182 (PROC)

The Bids and Awards Committee c/o Procurement Unit TSU, Tarlac City (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
1	unit	CAMERA LENS, "30MM F1.4 DC DN (F/SE) compatible to SONY E mount Sony E Mount/APS-C Format 45mm (35mm Equivalent) Aperture Range: f/1.4 to f/16 Three Aspherical Surfaces One High-Refractive Index Element Super Multi-Layer Coating Stepping AF Motor Rounded 9-Blade Diaphragm TSC Construction, Brass Bayonet Mount"	1		
2	unit	CAMERA LENS, 16MM F1.4 DC DN CONTEMPORARY LENS FOR SONY E MOUNT PRODUCT HIGHLIGHTS, E-Mount Lens/APS-C Format, 24mm (35mm Equivalent), Aperture Range: f/1.4 to f/16, 3 FLD, 2 SLD, and 2 Aspherical Elements, Super Multi-Layer Coating, Stepping AF Motor, Rounded 9-Blade Diaphragm, Weather-Sealed TSC Construction, Camera/Video Camera, Mount Sony E, Mount/APS-C Format, Lens, Filter Size Front: 67 mm, Focal Length 16mm Comparable 35mm Focal Length: 24 mm Aperture Maximum: f/1.4 Minimum: f/16, Angle of View 83.2* General, Compatibility Sony E Mount/APS-C Format/APS-C Format, Warranty 1 Year Manufacturer	1		

Format, War	ranty 1 Year Manuracturer				
Warranty			-		
The above-quoted price is inc	lusive of all costs ar	nd applicable tax	es		
Very truly yours,					
AUTHORIZED REPRESENTA	ATIVE:				
Signature Printed Name Date : Company Name Registered E-mail Address Contact no. :			- - - -		
BANK DETAILS:					
Bank Name	•		_		
Bank Address			_		
Bank Account Name	:		-		
Bank Account Number	:		_		
Form No.: TSU-PRO-SF-06	Revision No.: 06	Effectivity Date	: March 5, 2020)	Page 2 of 7

Date:	5/18/2023
RFQ No.	319-2023
PR No.	2023-05-182 (PROC)

The Bids and Awards Committee c/o Procurement Unit TSU, Tarlac City (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

3 unit	CAMERA TELESCOPIC JIB CRANE UPTO 240C, Load Capactiy: 4kg(full length), Total Length: 243cm, Front Crane Arm:		
4 unit	153cm, Back Crane Arm: 100cm Net Weight: 4.1kgJib Tilt Up: No LimitLib Tilt Down: No LimitCamera Tilt: Yes / By Tripod Head Tripod Require: Video Tripod W/ Head Package Includes: 1 x Telescopic Crane upto 240cm 1 x L Bracket for Camera Mount 1 x Quick Release Plate 1 x L Bracket for Tripod Mount 1 x Steel Cable for Tilting 1 x Handle Tube 2 x Steel Clip for Counter Weights 1 x Carrying BagM	1	
	CAMERA VIDEO SLIDER, Product Highlights Roller Bearing Sliding System, 50.7 lb Load Capacity, 47.2" Track Length, Tension-Adjustable Ball Bearings, Friction-Adjustable Knob, 3/8"-16 Tie-Down Screw, Detachable Legs with Rubber Ball Feet, Ruler for Precise & Repeatable Moves, Dual Oil Seals for Cleaning Rails, Carrying Bag , In the Box, Konova K5 Slider (47.2"), 2 x Oil Seals, 2 x Legs, 2 x Leg Pouch, Tuning Kit Features, 50.7 lb load capacity, Three steel bearings provide smooth, stable, and quiet operation, 8mm chrome-plated steel rails, Camera carriage with 3/8"-16 screw and two 1/4"-20 threaded holes, Friction-adjustment knob, Tension is adjustable using included wrench, 1/4"-20 and 3/8"-16 mounting threads at center and ends of tripods, Mounting threads on side of tripod for vertical mounting, Detachable height and angle- adjustable legs with rubber ball feet, Metric ruler for repeatable movements /4"-20 accessory mounting threads at each end of slider Dual oil seals help keep rails clean from dust and debris, Two bubble levels, Carrying bag Optional crank handle and motion control upgrade kits	1	

4					
Warranty :					
The above-quoted price is incl Very truly yours,	usive of all costs a	nd applicable taxe	∍s		
AUTHORIZED REPRESENTA	TIVE:				
Signature : Printed Name : Date : Company Name Registered E-mail Address Contact no. :	:				
BANK DETAILS: Bank Name : Bank Address : Bank Account Name : Bank Account Number					
Form No.: TSU-PRO-SF-06	Revision No.: 06	Effectivity Date:	March 5, 2020)	Page 3 of 7

Date:	5/18/2023
RFQ No.	319-2023
PR No.	2023-05-182 (PROC)

The Bids and Awards Committee c/o Procurement Unit TSU, Tarlac City (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

			7	UNIT PRICE	. •	
5	unit	CAMERA, Digital Camera with 15-45mm Kit, Image Sensor Type & Size: APS-C CMOS Sensor, Effective Pixels: Approx. 24.1 Megapixels, Image Processor: DIGIC 8, Focusing Method: Dual Pixel CMOS AF, Contrast AF (for 4K or 4K Time-lapse movie recording), ISO Speed (Recommended, Exposure Index): Stills: , Basic Zone: ISO speed set automatically, P, Tv, Av, M: ISO Auto, ISO 100–ISO 25600 set manually and ISO , expansion to H (Equivalent to ISO 51200), Movie Recording: ISO Auto, ISO 100–ISO 12800* set manually and ISO , expansion to H (Equivalent to ISO 16000/20000/25600), *4K and 4K Time-lapse movie: ISO 100-6400, Still Images: Aspect Ratios: 3:2, 4:3, 16:9, 1:1, Movie Recording Format: MP4, Movie Resolution & Frame Rate: 4K (3840 x 2160): 23.98p/25p, 4K Time-lapse: 29.97p/25p Full HD (1920 x 1080): 59.94p/50p/29.97p/25p, Full HD (1920 x 1080) Miniature Effect Movie, Video Snapshot: 29.97p/25p Full HD (1920 x 1080) Time-lapse: 29.97p/25p, HD (1280 x 720): 59.94p/50p, HD (1280 x 720) High Frame Rate Movies:, 119.88p/100p, HD (1280 x 720) High Frame Rate Movies:, 119.88p/100p, HD (1280 x 720) Hybrid Auto: 29.97p/25p, Built-in Flash: Retractable, Manual Pop-up Flash, Storage Media: SD, SDHC* and SDXC* memory cards *UHS-I cards compatible, Battery Type: Rechargeable Li-ion Battery Pack, Inclusions: 15-45mm Kit, Warranty: atleast 1-year warranty	2			

Warranty			
The above-quoted price is inc Very truly yours,	dusive of all costs a	nd applicable taxes	
AUTHORIZED REPRESENTA	ATIVE:		
Signature :			
Printed Name	·		
Date :			
Company Name Registered	•		
E-mail Address			
Contact no.			
BANK DETAILS:			
Bank Name	•		
Bank Address			
Bank Account Name	:		
Bank Account Number	:		
Form No.: TSU-PRO-SF-06	Revision No.: 06	Effectivity Date: March 5, 2020	Page 4 of 7

Page 5 of 7

PRICE QUOTATION

Date:	5/18/2023		
RFQ No.	319-2023		
PR No.	2023-05-182 (PROC)		

The Bids and Awards Committee c/o Procurement Unit TSU, Tarlac City (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
6	unit	CAMERA, Digital Camera, AF Modes: One-Shot AF, AI Servo AF, AI Focus AF, AF Point Selection Automatic selection, Manual selection, AF System Points: 9-point (Cross-type AF sensitive to f/5.6 with center AF point), Built-in Flash: YES, Closest Focusing Distance (cm): 25, Continuous Shooting Speed (Shots Per Sec) (Up To): 3, Dimensions (Excl. Protrusions) (mm) (Approx.): 129.0 x 101.3 x 77.6, Drive System: Micro Motor, Effective ISO: 100 - 6400 (H:12800), Effective Pixels (Megapixels): 24.1, Exposure Compensation: Manual: ±5 stops in 1/3- or 1/2-stop increments, AEB: ±2 stops in 1/3- or 1/2-stop increments, Flash Modes: E-TTL II Autoflash, FE Lock, Auto pop-up, Retractable, Built-in, Focal Length: (35mm Equivalent) 28.8 - 88mm(3x), Guide Number ISO 100 metres: 9.2/30.2, Image Resolution: 6000 x 4000 (L) 3984 x 2656 (M) 2976 x 1984 (S1) 1920 x 1280 (S2) 720 x 480 (S3) 6000 x 4000 (RAW), Image Stabilizer: Lens-shift type, LCD Monitor: (Size) (Inch) 3.0, LCD Monitor Resolutions (dots): 920000, Manual Focus YES, Memory Card Type: SD, SDHC*, SDXC*, *UHS-I cards compatible, Metering Mode: 63-zone TTL Evaluative, Partial, Spot, Centre-weighted average, Movie Format: MOV, Optical Zoom: 3x, Optional Power: AC Power (Compact Power Adapter CA-PS700 and DC Coupler DR-E10), Peripheral Connections: Hi-Speed USB, HDMI (Type C), Processor Type: DIGIC 4+, Sensor Size: APS-C, Shooting Modes: Scene Intelligent Auto, Flash Off, Creative Auto, Portrait, Landscape, Close-up, Sports, Food, Night Portrait, Program AE, Shutter-priority AE, Aperture-priority AE, Manual exposure Shutter Speed Range (Sec.) 30 - 1/4000, Bulb: Standard Power Supply, Battery Pack UP-E10 Still Image Format JPEG, RAW, RAW + JPEG Viewfinder Coverage (Approx.) 95 Viewfinder Type Eye level pentamirror Weight (g) (Including the battery and memory card) (Approx.) *For camera kits, weight includes kit lens(es). 675 White Balance Auto (Ambience priority), Auto (White priority), Preset (Daylight, Shade, Cloudy, Tungsten light, White fluorescent light, Flash), Custom Whi	1		

Warranty	I	
The above-quoted price is in Very truly yours,	nclusive of all costs ar	nd applicable taxes
AUTHORIZED REPRESEN	TATIVE:	
Signature Printed Name Date Company Name Registered E-mail Address Contact no.		
BANK DETAILS: Bank Name Bank Address Bank Account Name Bank Account Number		
Form No.: TSU-PRO-SF-06	Revision No.: 06	Effectivity Date: March 5, 2020

Date:	5/18/2023	
RFQ No.	319-2023	
PR No.	2023-05-182 (PROC)	

The Bids and Awards Committee c/o Procurement Unit TSU, Tarlac City (045) 982 -4630 / (045) 606 -8157

Sir / Madam:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
7	unit	CAMERA, DSLR COMPACT CAMERA, 83X optical zoom, 166x Dynamic Fine Zoom, 16.1-megapixel production, 3-in LCD monitor	1		
8	unit	C-STAND, 270CS C-STAND with Arm, Grip Head & Removable Turtle Base, Key Features, Light Stand Type: C-Stand with Boom .Stand Mobility: Without Wheels / Casters, Maximum Height: 270cm Max Height, Load Capacity: 10Kgs Max Load, Closed Length: 120cm Folded, Stand Weight: 7Kgs, Included Item List 1 x Godox C-Stand with Arm, Grip Head & Removable Turtle Base	6		
9	set	LED VIDEO LIGHT KIT, Photography Lighting Dimmable LED Video Light: 120pcs light beads provides 3200- 5600K color temperature, Each of 3 colors has 14-levels brightness to adjust. The light can flip in 180°, free to control. Adjustable Tripod Stand: Extendable support rod and tripod stand provides about 20cm-148cm working height, different height are to meet various lighting needs. 5 Filter Panels: Interchangeable white/ red/blue/ yellow/green filter panels are free to mount according to different portrait lighting needs, making light softer and more uniform. USB Powered: The light is powered with USB cable, connect to AC power adapter is recommended as the light demands high power consumption. Wide Application: Equipped with triple cold shoe mounts, the light is widely used in video lighting, live streaming, product portrait, for both table or ground settle. Color Temperature: 3200K-5600K Brightness: 14-level dimmable Lamp Bead Quantity: 120pcs Light Power Supply: USB cable Tripod Working Height: 11-13.5cm Total Working Height: About 20-148cm / 7.87-58.27in Light Dimension: 15 * 10 * 2.3cm / 5.91 * 3.94 * 0.91in Package Size: 32 * 18 * 4cm / 12.60 * 7.09 * 1.57in Package Weight: 470g / 16.58oz	4		

Warranty :			
The above-quoted price is incl Very truly yours,	usive of all costs ar	nd applicable taxes	
AUTHORIZED REPRESENTA	TIVE:		
Signature Printed Name Date Company Name Registered E-mail Address Contact no. BANK DETAILS: Bank Name Bank Address Bank Account Name Eank Account Number			
Form No.: TSU-PRO-SF-06	Revision No.: 06	Effectivity Date: March 5, 2020	Page 6 of 7

Date:	5/18/2023			
RFQ No.	319-2023			
PR No.	2023-05-182 (PROC)			

The Bids and Awards Committee c/o Procurement Unit TSU, Tarlac City

(045) 982 -4630 / (045) 606 -8157

Sir / Madam:

ITEM NO.	UNIT	ITEM & DESCRIPTION	QUANTITY	UNIT PRICE	TOTAL PRICE
10	unit	MONITOR HEADPHONES, Black Type Closed-back dynamic, Driver Diameter 45 mm Frequency Response 15 - 28,000 Hz, Maximum Input Power 1,600 mW at 1 kHz, Sensitivity 99 dB, Impedance 38 ohms Weight 285 g (10 oz), without cable and connector, Cable Interchangeable cables: detachable 1.2 m - 3.0 m (3.9' - 9.8') coiled cable, detachable 3.0 m (9.8') straight cable and detachable 1.2 m (3.9') straight cable, Cable - Detachable Yes, Connector Gold-plated stereo 1/8" (3.5 mm) connector with strain relief, Magnet Neodymium, Voice Coil CCAW (Copper-clad aluminum wire), Folding/collapsible Yes Accessories Included Protective carrying pouch, 6.3 mm (1/4") screw-	7		
11	piece	TRIPOD, Camera Tripod Monopod 60 inch Overhead Aluminum Lightweight DSLR Tripod with Horizontal Rod [Transverse Center Column] Central column moves from 0 to 180 degrees, can be rotated 360°horizontally, to realize panorama shooting. [Strong Stability] The weight of tripod is 1.65kg. 25mm large diameter aluminum alloy tube, the load capacity can reach 22.04lbs (10kg), provide security and stability support for your dslr Canon Nikon camera. [Compact & Flexible] 5 sections leg can adjust the height from 15.35" to 60.62"; the N. weight with ball head is only 3.63lbs; can be 180°reflexed, which is super portable with tripod carrying bag. [Metal Ball Head] Can be rotated 360 degrees, helping to expand camera activity range when panoramic shooting (the bubble level help to judge the level and the accurate composition) [Detachable Monopod] It can be turned into a monopod or walking stick alone to make your photography more diverse. (Note: For a camera with a telephoto zoom lens, you need to buy a tripod mount ring additionally or a telephoto lens bracket for better balance). Note: two types of quick release plates will be shipped randomly.	1		

		camera with a ring additional	nake your photography more telephoto zoom lens, you nee y or a telephoto lens bracket uick release plates will be ship	d to buy a tripod mount for better balance) . Note:		
Warranty			·		-	
Very truly			usive of all costs a	nd applicable tax	es	
Signature Printed Na Date	ame	: :				
	Name Reg I dress	istered :			· ·	
Contact no BANK DE	_	:				
Bank Nam Bank Add		:			-	
	ount Name				-	 ***
Form No.: TS	U-PRO-SF-06		Revision No.: 06	Effectivity Date:	March 5, 2020	Page 7 of





Central Portal for Philippine Government Procurement Oppurtunities

Bid Notice Abstract

Request for Quotation (RFQ)

Reference Number

9779368

Procuring Entity

TARLAC STATE UNIVERSITY

Title

Various Photographic Parts, Supplies and Accessories

Area of Delivery

Tarlac

Solicitation Number:	319-2023	Status	Pending
Trade Agreement:	Implementing Rules and Regulations		
Procurement Mode:	Negotiated Procurement - Small Value Procurement (Sec. 53.9)	Associated Components	3
Classification:	Goods	Pid Supplements	
Category:	Photographic Parts, Supplies and Accessories	Bid Supplements	Ü
Approved Budget for the Contract:	PHP 483,000.00	Document Request List	0
Delivery Period:	30 Day/s		
Client Agency:			24/05/2023
Contact Person:	Tutchie Panlilio Clerk	Date Published	24/03/2023
	TSU, Romulo Blvd. San Vicente, Tarlac City, Philippines Tarlac City Tarlac	Last Updated / Time	23/05/2023 10:37 AM
	1anac Philippines 2300 63-2-092058494963	Closing Date / Time	29/05/2023 13:00 PM
	elenamayteofilo73@gmail.com		

Description

for University use

2017	k i stam i popolije žakonostije se i Propolije se	e de la companya del companya de la companya del companya de la c	ing and the second		and the second
1	CAMERA LENS, "30MM F1.4 DC DN (F/SE)	compatible to SONY E mount Sony E Mount/APS-C Format 45mm (35mm Equivalent) Aperture Range: f/1.4 to f/16 Three Aspherical Surfaces One High-Refractive Index Element Super Multi-Layer Coating Stepping AF Motor Rounded 9-Blade Diaphragm TSC Constructi	1	Unit	25,000.00
2	CAMERA LENS, 16MM F1.4 DC DN	CONTEMPORARY LENS FOR SONY E MOUNT PRODUCT HIGHLIGHTS, E-Mount Lens/APS-C Format, 24mm (35mm Equivalent), Aperture Range: f/1.4 to f/16, 3 FLD, 2 SLD, and 2 Aspherical Elements, Super Multi-Layer Coating, Stepping AF Motor, Rounded 9-Blade Diaphragm	1	Unit	35,000.00
3	CAMERA TELESCOPIC JIB CRANE UPTO 240C	Load Capactiy: 4kg(full length), Total Length: 243cm, Front Crane Arm: 153cm, Back Crane Arm: 100cm Net Weight: 4.1kgJib Tilt Up: No LimitJib Tilt Down: No LimitCamera Tilt: Yes / By Tripod Head Tripod Require: Video Tripod W/ Head Package Includes	1	Unit	30,000.00
4	CAMERA VIDEO SLIDER	Product Highlights Roller Bearing Sliding System, 50.7 lb Load Capacity, 47.2" Track Length, Tension-Adjustable Ball Bearings, Friction-Adjustable Knob,	1	Unit	30,000.00

	printableBidNoticeAbstrac	,L		
	3/8"-16 Tie-Down Screw, Detachable Legs with Rubber Ball Feet, Ruler for Precise & Repeatable Mo			
CAMERA, Digital Camera with 15- 45mm Kit	Image Sensor Type & Size: APS-C CMOS Sensor, Effective Pixels: Approx. 24.1 Megapixels, Image Processor:DIGIC 8, Focusing Method: Dual Pixel CMOS AF, Contrast AF (for 4K or 4K Time-lapse movie recording), ISO Speed (Recommended, Exposure Index): St	2	Unit	75,000.00
CAMERA, Digital Camera	AF Modes: One-Shot AF, AI Servo AF, AI Focus AF, AF Point Selection Automatic selection, Manual selection, AF System Points: 9-point (Cross-type AF sensitive to f/5.6 with center AF point), Built-in Flash: YES, Closest Focusing Distance (cm): 25,	1	Unit	37,000.00
CAMERA, DSLR COMPACT CAMERA,	83X optical zoom, 166x Dynamic Fine Zoom, 16.1-megapixel production, 3-in LCD monitor	1	Unit	35,000.00
C-STAND,	270CS C-STAND with Arm, Grip Head & Removable Turtle Base, Key Features, Light Stand Type: C-Stand with Boom .Stand Mobility: Without Wheels / Casters, Maximum Height: 270cm Max Height, Load Capacity: 10Kgs Max Load, Closed Length: 120cm Folded, Sta	6	Unit	60,000.00
LED VIDEO LIGHT KIT	Photography Lighting Dimmable LED Video Light: 120pcs light beads provides 3200-5600K color temperature, Each of 3 colors has 14-levels brightness to adjust. The light can flip in 180°, free to control. Adjustable Tripod Stand: Extendable support ro	4	Set	6,000.00
MONITOR HEADPHONES	Black Type Closed-back dynamic, Driver Diameter 45 mm Frequency Response 15 - 28,000 Hz, Maximum Input Power 1,600 mW at 1 kHz, Sensitivity 99 dB, Impedance 38 ohms Weight 285 g (10 oz), without cable and connector, Cable Int	7	Unit	140,000.00
TRIPOD	Camera Tripod Monopod 60 inch Overhead Aluminum Lightweight DSLR Tripod with Horizontal Rod [Transverse Center Column] Central column moves from 0 to 180 degrees, can be rotated 360°horizontally, to realize panorama shooting. [Strong Stability] The we	1	Piece	10,000.00
	CAMERA, Digital CAMERA, DSLR COMPACT CAMERA, C-STAND, LED VIDEO LIGHT KIT MONITOR HEADPHONES	3/8"-16 Tie-Down Screw, Detachable Legs with Rubber Ball Feet, Ruler for Precise & Repeatable Mo CAMERA, Digital Camera with 15-45mm Kit	3/8"-16 Tie-Down Screw, Detachable Legs with Rubber Ball Feet, Ruler for Precise & Repeatable Mo	3/8*-16 Tie-Down Screw, Detachable Legs with Rubber Ball Feet, Ruler for Precise & Repeatable Mo

Other Information

The bidders must download the attached documents in the associated component section.

Created by

Tutchie Panlilio

Date Created

23/05/2023

The PhilGEPS team is not responsible for any typographical errors or misinformation presented in the system. PhilGEPS only displays information provided for by its clients, and any queries regarding the postings should be directed to the contact person/s of the concerned party.

© 2004-2023 DBM Procurement Service. All rights reserved.

Help | Contact Us | Sitemap